



14 cm

12 dB



ICE Model



Revolutionary 15 air-guiding Fan Blades for unprecedented airflow performance with ultra-low noise level.

Exclusive FLUXUS PRO II bearing based in Fluid Dynamic Bearing Technology for more than 200.000 hrs lifespan and ultra-silent operation.

- Special Voltage reduction cable included for Ultra-performance or Ultra-quiet operation.
- Professional Anti-vibration screws, 3-4pin adaptor and black sleeved cables included.
- Ultra-silent: 12dB-20dB and Ultra-Airflow: 50-90 CFM

Standard Connection

Rated Voltage:	12V
Starting Voltage:	≤ 6.0V
Power Consumption:	3.6W
Rated Current:	0.30A
Speed:	1200 RPM±10%
Air Flow:	90 CFM
Air Pressure:	0.931 mm -H ₂ O
Noise:	20dBA
MTBF:	200.000 hours

Connect with Voltage reduction cable

Rated Voltage:	(To FAN) 7V
Starting Voltage:	≤ 6.0V
Power Consumption:	1.56W
Rated Current:	0.13A
Speed:	700 RPM±10%
Air Flow:	50 CFM
Air Pressure:	0.414 mm -H ₂ O
Noise:	12dBA
MTBF:	200.000 hours

DESIGNED IN EUROPE